


PRODUCT-DETAILS

# MARL110AR

## MARL110AR Auxiliary Contact Block



### General Information

Extended Product Type	MARL110AR
Product ID	1SAL103356R9906
EAN	4013614552335
Catalog Description	MARL110AR Auxiliary Contact Block
Long Description	MARL110AR Auxiliary Contact 1NO ring tongue terminal, side mounted EN 50005

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

### Popular Downloads

Instructions and Manuals	2CDC102076M9901
--------------------------	-----------------

### Dimensions

Product Net Width	9.8 mm
Product Net Height	42.5 mm
Product Net Depth / Length	56 mm
Product Net Weight	0.017 kg

## Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 440 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U <sub>i</sub> )	750 V
Degree of Protection	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup> Rigid 1/2x 0.75 ... 2.5 mm <sup>2</sup>
Tightening Torque	Auxiliary Circuit 0.8 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 UL 60947-5-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I <sub>th</sub> )	Auxiliary Circuit 10 A
Product Name	Auxiliary Contact Block
Suitable For	MC1 MC2 MCR
Suitable for Product Class	Mini Contactors

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in·lb

## Environmental

Ambient Air Temperature	Operation -40 ... +55 °C Storage -55 ... +80 °C
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU

---

## Certificates and Declarations (Document Number)

---

BV Certificate	BV_M_Range
CB Certificate	1SAA971002-2001
CCC Certificate	CCC_MARL_MACL
cULus Certificate	cUL_E48139
Declaration of Conformity - CE	1SAD938502-0305
EAC Certificate	1SAA971002-2701
Instructions and Manuals	2CDC102076M9901
RINA Certificate	1SAA971000-0201
RoHS Information	1SAD038501-0305

---



---

## Container Information

---

Package Level 1 Width	99 mm
Package Level 1 Depth / Length	20 mm
Package Level 1 Height	100 mm
Package Level 1 Gross Weight	0.02 kg
Package Level 1 EAN	4013614552335
Package Level 1 Units	bag 1 piece
Package Level 2 Width	100 mm
Package Level 2 Depth / Length	150 mm
Package Level 2 Height	105 mm
Package Level 2 Gross Weight	0.22 kg
Package Level 2 EAN	4013614552373
Package Level 2 Units	box 10 piece

---



---

## Classifications

---

Object Classification Code	K
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522

---



---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

