


PRODUCT-DETAILS

# MC1CC00ATWL

## MC1CC00ATWL Mini Contactor 3NO+1NC

125VDC +/-30%



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | MC1CC00ATWL  |
| Product ID            | 1SAL200798R9901  |
| EAN                   | 4013614543142  |
| Catalog Description   | MC1CC00ATWL Mini Contactor 3NO+1NC 125VDC +/-30%   |
| Long Description      | The MC1CC00ATWL mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is equipped with an extended operating limits coil and it's suitable for wall or rail mounting. |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85365080 |

### Popular Downloads

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 2CDC103061M6801 |
|--------------------------|-----------------|

### Dimensions

|                   |       |
|-------------------|-------|
| Product Net Width | 45 mm |
|-------------------|-------|

|                            |         |
|----------------------------|---------|
| Product Net Height         | 48 mm   |
| Product Net Depth / Length | 68 mm   |
| Product Net Weight         | 0.25 kg |

## Technical

|  |  |
|--|--|
| Number of Poles                                    | 4  |
| Mini Contactor Type                                | Mini Contactor   |
| Rated Operational Voltage                          | Main Circuit 690 V AC<br>Main Circuit 440 V DC   |
| Rated Frequency (f)                                | Control Circuit DC<br>Main Circuit 50 Hz<br>Main Circuit 60 Hz<br>Main Circuit DC  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | Main Circuit 6 kV  |
| Rated Insulation Voltage ( $U_i$ )                 | 750 V  |
| Number of Main Contacts NC                         | 1  |
| Number of Main Contacts NO                         | 3  |
| Rated Operational Current AC-1 ( $I_e$ )           | (230 V) 55 °C 20 A<br>(230 V) 70 °C 16 A<br>(400 V) 55 °C 20 A<br>(400 V) 70 °C 16 A<br>(500 V) 55 °C 20 A<br>(500 V) 70 °C 16 A<br>(690 V) 55 °C 20 A<br>(690 V) 70 °C 16 A   |
| Rated Operational Power AC-3 ( $P_e$ )             | (230 V) Single Phase 1.1 kW<br>(230 V) Three Phase 2.2 kW<br>(400 V) Three Phase 4 kW<br>(500 V) Three Phase 4 kW<br>(690 V) Three Phase, NC 3 kW<br>(690 V) Three Phase, NO 4 kW  |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 72 A  |
| Number of Auxiliary Contacts NC                    | 0  |
| Number of Auxiliary Contacts NO                    | 0  |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | Main Circuit 20 A  |
| Rated Control Circuit Voltage ( $U_c$ )            | 125 V DC   |
| Coil Operating Limits                              | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55$ °C)  |
| Degree of Protection                               | Control Circuit Terminals IP20<br>Main Circuit Terminals IP20  |
| Mechanical Durability                              | 10000000 cycle   |
| Maximum Electrical Switching Frequency             | AC-1 300 cycles per hour<br>AC-15 360 cycles per hour<br>AC-3 1200 cycles per hour<br>DC-1 600 cycles per hour<br>DC-13 360 cycles per hour<br>DC-3 600 cycles per hour  |
| Connecting Capacity Main Circuit                   | Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1x 0.75 ... 4 mm <sup>2</sup><br>Rigid 2x 0.75 ... 2.5 mm <sup>2</sup> |
| Connecting Capacity Control Circuit                | Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup>  |

|                       |  |
|-----------------------|--|
|                       | Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 0.75 ... 2.5 mm <sup>2</sup> |
| Wire Stripping Length | Control Circuit 9 mm<br>Main Circuit 9 mm  |
| Tightening Torque     | Control Circuit 0.8 N·m<br>Main Circuit 0.8 ... 1.0 N·m  |
| Mounting on DIN Rail  | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715   |
| Power Loss            | at Rated Operating Conditions AC-1 per Pole 0.7 W  |
| Standards             | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>UL 60947-1<br>UL 60947-4-1   |

## Technical UL/CSA

|   |  |
|---|--|
| Maximum Operating Voltage UL/CSA        | Main Circuit 600 V AC  |
| Full Load Amps Motor Use                | (115 V AC) Single Phase 9.8 A<br>(200 V AC) Three Phase 11 A<br>(230 V AC) Single Phase 10 A<br>(240 V AC) Three Phase 9.6 A<br>(380 ... 415 V AC) Three Phase 6.1 A<br>(440 ... 480 V AC) Three Phase 7.6 A<br>(550 ... 600 V AC) Three Phase 6.1 A |
| Horsepower Rating UL/CSA                | (115 V AC) Single Phase 0.5 Hp<br>(200 V AC) Three Phase 3 Hp<br>(230 V AC) Single Phase 1.5 Hp<br>(240 V AC) Three Phase 3 Hp<br>(380 ... 415 V AC) Three Phase 3 Hp<br>(440 ... 480 V AC) Three Phase 5 Hp<br>(550 ... 600 V AC) Three Phase 5 Hp  |
| General Use Rating UL/CSA               | (600 V AC) 20 A  |
| Connecting Capacity Main Circuit UL/CSA | Stranded 1/2x 18-12 AWG  |
| Tightening Torque UL/CSA                | Control Circuit 7 in·lb<br>Main Circuit 7 in·lb  |

## Environmental

|  |  |
|--|--|
| Ambient Air Temperature                        | Operation -40 ... +55 °C<br>Storage -55 ... +80 °C |
| Maximum Operating Altitude Permissible         | 3000 m   |
| Resistance to Shock acc. to IEC 60068-2-27     | 11 ms Pulse 25g                                    |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 3 ... 150 Hz                                  |
| RoHS Status                                    | Following EU Directive 2011/65/EU                  |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| BV Certificate                 | BV_M_Range      |
| CB Certificate                 | 1SAA971000-2001 |
| CCC Certificate                | CCC_MC1_MC2     |
| cULus Certificate              | cUL_E191658     |
| Declaration of Conformity - CE | 1SAD938502-0305 |
| EAC Certificate                | 1SAA971000-2701 |
| Instructions and Manuals       | 2CDC103061M6801 |
| RINA Certificate               | 1SAA971000-0201 |

---

## Container Information

---

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 46 mm         |
| Package Level 1 Height         | 70 mm         |
| Package Level 1 Depth / Length | 49 mm         |
| Package Level 1 Gross Weight   | 0.255 kg      |
| Package Level 1 EAN            | 4013614543142 |
| Package Level 2 Units          | box 10 piece  |
| Package Level 2 Width          | 243 mm        |
| Package Level 2 Height         | 80 mm         |
| Package Level 2 Depth / Length | 106 mm        |
| Package Level 2 Gross Weight   | 2.61 kg       |
| Package Level 2 EAN            | 4013614543654 |

---

## Classifications

---

|                            |   |
|----------------------------|---|
| Object Classification Code | Q   |
| ETIM 5                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                     | EC000066 - Power contactor, AC switching  |
| ETIM 7                     | EC000066 - Power contactor, AC switching  |
| eClass                     | 7.0 27371003                              |
| UNSPSC                     | 39121529                                  |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

