

PRODUCT-DETAILS

AF63-30-11 20-60V DC

AF63-30-11 20-60V DC Contactor



General Information

Extended Product Type	AF63-30-11 20-60V DC
Product ID	1SBL377001R7211
EAN	3471522115027
Catalog Description	AF63-30-11 20-60V DC Contactor

Long Description	<p>AF63 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC and 220 V DC. The contactors can also be used for many other applications such as bypass, capacitor switching, lighting, DC power circuits... The AF... contactors are fitted with an electronic coil interface which accepts a wide control voltage range, on AC 50/60 Hz or DC supplies. The same contactor can accept various supply voltages according to the different countries where the electrical equipment will be installed, or some fluctuation in the control voltage due to the local supply or network. The AF... contactors are also fully suitable for operation in AC or DC control circuit liable to voltage interruptions or voltage dip risks. Advantages: - Wide voltage range, e.g. 100 ... 250 V AC and DC - Can manage large voltage variations - Reduced power consumption - Very distinct closing and opening - Noise free - Can withstand voltage interruptions or voltage dips in the control supply (≤ 20 ms). The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles and 2 built-in auxiliary contacts, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.</p>
------------------	---

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching

ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	140 mm
Package Level 1 Depth / Length	146 mm
Package Level 1 Height	96 mm
Package Level 1 Gross Weight	1.22 kg
Package Level 1 EAN	3471522115027
Package Level 2 Units	box 20 piece
Package Level 2 Gross Weight	24.4 kg

Certificates and Declarations (Document Number)

CB Certificate	CB_CN45489
CCC Certificate	CCC_2018010304134049 CCC_2010010304402983
CSA Certificate	CSA_1033838_LR056745
Declaration of Conformity - CE	1SBD250803U1000
EAC Certificate	EAC_RU C-FR ME77 B01010
Environmental Information	1SBD250021E1002
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407734P0003
KC Certificate	KC_HW02016-18015B
RoHS Information	1SBD250803U1000
UL Certificate	UL_20120830-E312527-10-1
UL Listing Card	UL_E312527

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Close to Contactor without Thermal O/L Relay -40 ... +70 °C Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU

Technical

Number of Main Contacts NO	3
Number of Main Contacts	0

NC

Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Supply Circuit 50 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, $q = 40\text{ }^{\circ}\text{C}$ 16 A acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ }^{\circ}\text{C}$ 125 A
Rated Operational Current AC-1 (I_e)	(690 V) $40\text{ }^{\circ}\text{C}$ 115 A (690 V) $55\text{ }^{\circ}\text{C}$ 95 A (690 V) $70\text{ }^{\circ}\text{C}$ 80 A
Rated Operational Current AC-3 (I_e)	(220 / 230 / 240 V) $55\text{ }^{\circ}\text{C}$ 65 A (380 / 400 V) $55\text{ }^{\circ}\text{C}$ 65 A (415 V) $55\text{ }^{\circ}\text{C}$ 65 A (440 V) $55\text{ }^{\circ}\text{C}$ 65 A (500 V) $55\text{ }^{\circ}\text{C}$ 55 A (690 V) $55\text{ }^{\circ}\text{C}$ 43 A
Rated Operational Power AC-3 (P_e)	(220 / 230 / 240 V) 18.5 kW (380 / 400 V) 30 kW (415 V) 37 kW (440 V) 37 kW (500 V) 37 kW (690 V) 37 kW
Rated Operational Power AC-6b (P_e)	(230 / 240 V) $40\text{ }^{\circ}\text{C}$, 50 / 60 Hz 25 kvar (230 / 240 V) $55\text{ }^{\circ}\text{C}$, 50 / 60 Hz 25 kvar (230 / 240 V) $70\text{ }^{\circ}\text{C}$, 50 / 60 Hz 23 kvar (400 / 415 V) $40\text{ }^{\circ}\text{C}$, 50 / 60 Hz 43 kvar (400 / 415 V) $70\text{ }^{\circ}\text{C}$, 50 / 60 Hz 39 kvar (400 / 415 V) $55\text{ }^{\circ}\text{C}$, 50 / 60 Hz 43 kvar (440 V) $40\text{ }^{\circ}\text{C}$, 50 / 60 Hz 47 kvar (440 V) $55\text{ }^{\circ}\text{C}$, 50 / 60 Hz 47 kvar (440 V) $70\text{ }^{\circ}\text{C}$, 50 / 60 Hz 42.5 kvar (500 / 550 V), $40\text{ }^{\circ}\text{C}$, 50 / 60 Hz 54 kvar (500 / 550 V) $55\text{ }^{\circ}\text{C}$, 50 / 60 Hz 54 kvar (500 / 550 V) $70\text{ }^{\circ}\text{C}$, 50 / 60 Hz 48.5 kvar (690 V) $40\text{ }^{\circ}\text{C}$, 50 / 60 Hz 74 kvar (690 V) $55\text{ }^{\circ}\text{C}$, 50 / 60 Hz 74 kvar (690 V) $70\text{ }^{\circ}\text{C}$, 50 / 60 Hz 67 kvar
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Rated Operational Current AC-15 (I_e)	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 125 A
Maximum Breaking Capacity	$\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 440 V 1300 A $\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 690 V 630 A
Maximum Electrical Switching Frequency	AC-1 300 cycles per hour AC-2 / AC-4 150 cycles per hour AC-3 300 cycles per hour
Rated Operational Current DC-13 (I_e)	(125 V) 0.55 / 69 A (24 V) 6 / 144 A (250 V) 0.3 / 75 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A
Rated Insulation Voltage	acc. to UL/CSA 600 V

(U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Rated Control Circuit Voltage (U _c)	DC Operation 20 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 7 2.8 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 7 2.8 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 210 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 210 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 35 ... 115 ms Between Coil De-energization and NO Contact Opening 30 ... 110 ms Between Coil Energization and NC Contact Opening 27 ... 95 ms Between Coil Energization and NO Contact Closing 30 ... 100 ms
Connecting Capacity Main Circuit	Flexible with Cable End 6 ... 16 m ² Rigid Cable 6 ... 25 m ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 m ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector
Terminal Type	Screw Terminals

Dimensions

Product Net Width	82 mm
Product Net Depth / Length	108 mm
Product Net Height	110 mm
Product Net Weight	1.22 kg

Popular Downloads

Data Sheet, Technical Information	1SNC001003C0202
Instructions and Manuals	FPTC407734P0003

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

