

PRODUCT-DETAILS

# OTDC32FT3

## OTDC32FT3 DC Switch-disconnector



### General Information

Extended Product Type	OTDC32FT3
Product ID	1SCA123846R1001
EAN	6417019545653
Catalog Description	OTDC32FT3 DC Switch-disconnector
Long Description	OTDC32FT3 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Door mounting, IEC 1000 VDC 32 A single circuit

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030

### Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301079M0206
Mechanical Drawings	OTDC16-32FT3_palikkamalli.igs 1SCC307021F0003 1SCC307022F0003

---

## Dimensions

---

Product Frame Size	XS
Product Net Width	52.5 mm 2.1 in
Product Net Height	69 mm 2.7 in
Product Net Depth / Length	75.5 mm 3 in
Product Net Weight	0.2 kg 0.4 lb

---



---

## Technical

---

Rated Operational Current DC-21B ( $I_e$ )	(600 V) 36 A (1000 V) 32 A
Conventional Free-air Thermal Current ( $I_{th}$ )	45 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 45 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(1000 V DC) 0.8 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	(1000 V DC) 0.8 kA for 1 s 0.8 kA
Power Loss	at Rated Operating Conditions per Pole 0.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Shaft Diameter	6 mm 0.24 in
Switches Operating Mechanism	Mechanism on Top of the Switch
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Door mounting
Number of Circuits	1
Number of Poles	3
Cable Cross-Section	2.5 ... 16 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	1.2...1.4 N·m

---



---

## Environmental

---

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	NA

---

### Certificates and Declarations (Document Number)

CCC Certificate	CCC OTDC16-32.pdf
Declaration of Conformity - CE	1SCC301192D2704
DNV GL Certificate	1SCC301231D0201
Environmental Information	NA
Instructions and Manuals	1SCC301079M0206
RoHS Information	1SCC301207D0203

---

### Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	90 mm 3.5 in
Package Level 1 Depth / Length	54 mm 2.1 in
Package Level 1 Height	90 mm 3.5 in
Package Level 1 Gross Weight	0.2 kg 0.5 lb
Package Level 1 EAN	6417019545653

---

### Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

### Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

