

PRODUCT-DETAILS

XT6H 800 TMA 630-6300 4p F F InN=100%In

XT6H 800 TMA 630-6300 4p F F InN=100%In



General Information

Extended Product Type	XT6H 800 TMA 630-6300 4p F F InN=100%In
Product ID	1SDA107595R1
EAN	8015644102487
Catalog Description	XT6H 800 TMA 630-6300 4p F F InN=100%In
Long Description	C.BREAKER TMAX XT6H 800 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE FOUR-POLE IN AC-DC TMA R 630 I3=3150...6300 A FULLY RATED NEUTRAL

Ordering

EAN	8015644102487
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	12 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	305 mm
Package Level 1 Height	285 mm
Package Level 1 Depth / Length	370 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	8015644102487

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Configuration Type	Loose or configurable
Current Type	AC/DC
Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Power Loss	34.4 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	630 A
Rated Frequency (f)	50/60 Hz
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I_s)	3150...6300 A
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 25 kA (250 V DC) 2 Poles in Series 35 kA (500 V DC) 2 Poles in Series 25 kA (750 V DC) 3 Poles in Series 18 kA
Rated Short-time Withstand Current (I_{cw})	10 kA
Rated Ultimate Short-	(220 V AC) 100 kA

Circuit Breaking Capacity (I_{cu})	(230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 25 kA (250 V DC) 2 Poles in Series 70 kA (500 V DC) 2 Poles in Series 50 kA
Rated Uninterrupted Current (I_u)	800 A
Release	TMA
Release Type	TM
Setting Range	441...630 A
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	XT6
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK107680A2825
Instructions and Manuals	1SDH002012A1001

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

