

PRODUCT-DETAILS

S801HV-K10

S801HV-K10 High Performance MCB



General Information

Extended Product Type	S801HV-K10
Product ID	2CCF019007R0001
EAN	7612271436452
Catalog Description	S801HV-K10 High Performance MCB

Long Description

The S801HV-K10 is a 1-pole High Performance Circuit breaker with K-characteristic, with cage terminal, long separating plates and a rated current of 10 A. It is a current limiting device with a maximum breaking capacity of 4kA at 580/1000V. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S801HV-K10 complies with IEC/EN 60947-2 and allows the use for industrial applications. It can be used worldwide. The extensive range of accessory makes the use of S801HV-K10 more comfortable. Due to the fast arc extinction of S801HV-K10 your application will be secured.

Technical

Standards	IEC/EN 60947-2
Number of Poles	1
Number of Protected Poles	1
Tripping Characteristic	K
Rated Current (I_n)	10 A
Rated Operational Voltage	580/1000 V AC
Power Loss	1.5 W at Rated Operating Conditions per Pole 1.5 W

Rated Insulation Voltage (U _i)	1000 V AC
Rated Frequency (f)	50...60 Hz
Rated Short-Circuit Capacity (I _{cn})	(400 V) 2.5 kA (230 V) 2.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(580 / 1000 V AC) 4 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(580 / 1000 V AC) 2.5 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Housing Material	Insulation group I, RAL 7035
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Remarks	Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw
Terminal Type	Screw Terminals
Connecting Capacity	Rigid 0 ... 50 mm ² Flexible 0 ... 70 mm ²
Tightening Torque	3.5 N·m
Recommended Screw Driver	Pozidriv 2
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	Any
Built-In Depth (t ₂)	82.5 mm

Environmental

Ambient Air Temperature	Operation -25...60 °C
Resistance to Shock acc. to IEC 60068-2-27	5 g 30 ms
Resistance to Vibrations acc. to IEC 60068-2-6	2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x 1e
Environmental Conditions	Damp Heat Cyclic acc. to IEC 60068-2-30 12+12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96% Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100% Dry Heat Test B acc. to IEC 60068-2-2 16 hour @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hour @ 70 °C
RoHS Status	Following EU Directive 2011/65/EU

Dimensions

Product Net Width	27 mm
Product Net Depth / Length	82.5 mm
Product Net Height	142 mm
Product Net Weight	240 g

Container Information

Package Level 1 Units	box 1 piece
-----------------------	-------------

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	33 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	310 g
Package Level 1 EAN	7612271436452

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413009D0201
Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413016M0008
RoHS Information	2CCC413009D0201 9AKK107680A3903

Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413016M0008

Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

