

PRODUCT-DETAILS

S802B-D125

S802B-D125 High Performance MCB



General II	nformation
------------	------------

Extended Product Type	S802B-D125
Product ID	2CCS812001R0841
EAN	7612271416195
Catalog Description	S802B-D125 High Performance MCB

Catalog Description

S802B-D125 High Performance MCB

Long Description

The S802B-D125 is a 2-pole High Performance Circuit breaker with D-Dharacteristic, with cage terminal and a rated current of 125 A. It is a current limiting device with a maximum breaking capacity of 16kA at 230/400V. It can be used for voltages up to 230/400V. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802B-D125 complies with IEC/EN 60947-2 and EN 60898-1 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S802B-D125 more comfortable. Due to the fast arc extinction of S802B-D125 your application will be secured.

Technical

Standards	IEC/EN 60947-2
Number of Poles	2
Number of Protected Poles	2
Tripping Characteristic	D
Rated Current (I _n)	125 A
Power Loss	21.88 W at Rated Operating Conditions per Pole 10.94 W
Rated Insulation Voltage	acc. to IEC/EN 60664-1 500 V AC

 (U_i)

Rated Short-Circuit Capacity (I _{cn})	(400 V) 10 kA (230 V) 10 kA
Rated Ultimate Short- Circuit Breaking	(230 / 400 V AC) 16 kA (150 V DC) 10 kA
Capacity (I _{cu}) Rated Service Short-	(230 / 400 V AC) 10 kA
Circuit Breaking	(230 / 400 V AC) 10 KA
Capacity (I _{cs})	
Energy Limiting Class	
Overvoltage Category	II
Pollution Degree	3
Rated Impulse Withstand Voltage (U _{imp})	6 k\
Degree of Protection	IP20
Connecting Capacity	Rigid 0 50 mm Flexible 0 70 mm
Built-In Depth (t ₂)	82.5 mm
Environmental Application 1997	Occupation 25 CO 66
Ambient Air Temperature	Operation -2560 °C
RoHS Status	Following EU Directive 2011/65/EU
Dimensions	
Product Net Width	54 mm
Product Net Depth /	82.5 mm
Length	
Product Net Height	95 mm
Product Net Weight	490 <u>c</u>
Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	60 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	510 <u>c</u>
Package Level 1 EAN	7612271416195
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85362020
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	2CCC413016D0601
Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413016M0008
RoHS Information	2CCC413016D0601

Popular Downloads	
Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413016M0008

Classifications	
Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs$

