


PRODUCT-DETAILS

# S804S-UCK25

## S804S-UCK25 High Performance MCB



### General Information

Extended Product Type	S804S-UCK25
Product ID	2CCS864001R1517
EAN	7612271203726
Catalog Description	S804S-UCK25 High Performance MCB
Long Description	S804S-UCK25 High Performance Miniature Circuit Breaker 4 Poles K Characteristic 25A 50kA 250VDC

### Technical

Standards	IEC/EN 60947-2
Number of Poles	4
Number of Protected Poles	4
Tripping Characteristic	UC-K
Rated Current ( $I_n$ )	25 A
Rated Operational Voltage	1000 V DC
Power Loss	16.8 W at Rated Operating Conditions per Pole 4.2 W
Rated Insulation Voltage ( $U_i$ )	1500 V DC
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(1000 V DC) 50 kA
Rated Service Short-Circuit Breaking	(750 V DC) 50 kA

Capacity (I <sub>cs</sub> )	
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	8 kV
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 50 mm <sup>2</sup> Flexible 0 ... 70 mm <sup>2</sup>
Built-In Depth (t <sub>2</sub> )	82.5 mm

## Environmental

Ambient Air Temperature	Operation -25...60 °C
Environmental Conditions	Damp Heat Cyclic acc. to IEC 60068-2-30 388 + 12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96 % Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100 % Dry Heat Test B acc. to IEC 60068-2-2 16 hours @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hours @ 70 °C
RoHS Status	Following EU Directive 2011/65/EU

## Dimensions

Product Net Width	106 mm
Product Net Depth / Length	82.5 mm
Product Net Height	95 mm
Product Net Weight	980 g

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	111 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	1010 g
Package Level 1 EAN	7612271203726

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413016D0601
Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413016M0008

RoHS Information

2CCC413016D0601  
9AKK107680A3903

---

## Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413016M0008
Dimension Diagram	2CCC413003C0201

---

## Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

