

PRODUCT-DETAILS

## S202CL-C40

# Miniature Circuit Breakers MCBs - S200C - 2P - C - 40 ampere



### General Information

Extended Product Type	S202CL-C40
Product ID	2CDS242280R0404
EAN	4053546042535
Catalog Description	Miniature Circuit Breakers MCBs - S200C - 2P - C - 40 ampere
Long Description	S202CL-C40 Miniature Circuit Breaker C-char.,4.5kA, 40A, 2P 1M

### Technical

Standards	IEC/EN 60898-1
Number of Poles	2
Number of Protected Poles	2
Tripping Characteristic	C
Rated Current ( $I_n$ )	40 A
Rated Operational Voltage	415 V AC
Power Loss	8.9 W
Rated Frequency (f)	50 Hz 60 Hz
Rated Short-Circuit Capacity ( $I_{cn}$ )	4.5 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	6 kA
Electrical Endurance	10000 cycle

Connecting Capacity	20000 cycle Busbar 10 mm <sup>2</sup> Flexible 1 ... 10 mm <sup>2</sup> Rigid 1 ... 16 mm <sup>2</sup>
Power Supply Connection	Arbitrary

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
RoHS Status	Following EU Directive 2011/65/EU

## Dimensions

Product Net Width	18 mm
Product Net Depth / Length	70 mm
Product Net Height	86 mm
Product Net Weight	0.16 kg

## Container Information

Package Level 1 Units	carton 12 piece
Package Level 1 Width	217 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	92 mm
Package Level 1 Gross Weight	1.97 kg
Package Level 1 EAN	4053546044133

## Ordering

Minimum Order Quantity	12 piece
Customs Tariff Number	85362010

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107492A9802
RoHS Information	9AKK107492A9802

## Classifications

ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
eClass	7.0 27141901
UNSPSC	39121614

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

