

PRODUCT-DETAILS

S204CL-C20

Miniature Circuit Breakers MCBs - S200C - 4P - C - 20 ampere



General Information

Extended Product Type	S204CL-C20
Product ID	2CDS244280R0204
EAN	4053546042818
Catalog Description	Miniature Circuit Breakers MCBs - S200C - 4P - C - 20 ampere
Long Description	S204CL-C20 Miniature Circuit Breaker C-char.,4.5kA, 20A, 4P 2M

Technical

Standards	IEC/EN 60898-1
Number of Poles	4
Number of Protected Poles	4
Tripping Characteristic	C
Rated Current (I_n)	20 A
Rated Operational Voltage	415 V AC
Power Loss	10.1 W
Rated Frequency (f)	50 Hz 60 Hz
Rated Short-Circuit Capacity (I_{cn})	4.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	6 kA
Electrical Endurance	10000 cycle

	20000 cycle
Connecting Capacity	Busbar 10 mm ² Flexible 1 ... 10 mm ² Rigid 1 ... 16 mm ²
Power Supply Connection	Arbitrary

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
RoHS Status	Following EU Directive 2011/65/EU

Dimensions

Product Net Width	36 mm
Product Net Depth / Length	70 mm
Product Net Height	86 mm
Product Net Weight	0.32 kg

Container Information

Package Level 1 Units	carton 6 piece
Package Level 1 Width	217 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	92 mm
Package Level 1 Gross Weight	1.97 kg
Package Level 1 EAN	4053546044416

Ordering

Minimum Order Quantity	6 piece
Customs Tariff Number	85362010

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107492A9802
RoHS Information	9AKK107492A9802

Classifications

ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
eClass	7.0 27141901
UNSPSC	39121614

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

