

PRODUCT-DETAILS

PACS25/BL/25M

STD WGT BLK NYL COND NC25 25M



General Information

Extended Product Type	PACS25/BL/25M
Product ID	7TCA296000R1980
EAN	5020963029042
Catalog Description	STD WGT BLK NYL COND NC25 25M
Long Description	Non-Metallic Standard Weight Flexible Conduit, Nominal Conduit Size 25, Static Bend Radius 50 Millimeters, Coarse Pitch, Low Fire Hazard, Length 25 Meters, Polyamide 6, Black

Ordering

EAN	5020963029042
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	4.41 lb 2 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	24.5 in 622 mm

Package Level 1 Height	24.5 in 622 mm
Package Level 1 Depth / Length	20 in 508 mm
Package Level 2 Units	1 piece
Package Level 2 Width	40 in 1016 mm
Package Level 2 Height	50 in 1270 mm
Package Level 2 Depth / Length	48 in 1219 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Material	Polyamide/Nylon 6
Nominal Size	25 mm
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Coarse Pitch
Radius	50 mm
Special Functions	High Fatigue Life, Self Extinguishing, Halogen Free
UPC	786210267524

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PACS25/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PACS25/BL/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

