

PRODUCT-DETAILS

PACS54/BL/10M

STD WGT BLK NYL COND 10M NC54



General Information

Extended Product Type	PACS54/BL/10M
Product ID	7TCA296000R2031
EAN	5020963005237
Catalog Description	STD WGT BLK NYL COND 10M NC54
Long Description	Standard Weight Conduit, Nominal Conduit Size 54mm, NW Conduit Size 48, Coarse Conduit Pitch, Outside Diameter 54.5mm, Inside Diameter 46.5mm, Static Bend Radius 75mm, Reel Length 10 Meters, Polyamide (Nylon) 6, Black

Ordering

EAN	5020963005237
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	5.32 lb 2.413 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	24.5 in 622 mm

Package Level 1 Height	50 in 1270 mm
Package Level 1 Depth / Length	24.5 in 622 mm
Package Level 2 Units	1 piece
Package Level 2 Width	40 in 1016 mm
Package Level 2 Height	50 in 1270 mm
Package Level 2 Depth / Length	48 in 1219 mm
Package Level 3 Units	18 piece

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	46.5 mm
Material	Polyamide/Nylon 6
Nominal Size	54 mm
Number of Batteries	0
Outside Diameter	54.5 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Coarse Pitch
Radius	75 mm
Special Functions	High Fatigue Life, Self Extinguishing, Halogen Free
UPC	786210147352

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PACS54/BL/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PACS54/BL/10M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

