

PRODUCT-DETAILS

PAFS16/GR/50M

STD WGT GRY NYL COND NC16 50M



General Information

Extended Product Type	PAFS16/GR/50M
Product ID	7TCA296000R2186
EAN	5020963000645
Catalog Description	STD WGT GRY NYL COND NC16 50M
Long Description	Standard Weight Conduit, Nominal Conduit Size 16mm, NW Conduit Size 13, Fine Conduit Pitch, Outside Diameter 15.8mm, Inside Diameter 11.8mm, Static Bend Radius 35mm, Reel Length 50 Meters, Polyamide (Nylon) 6, Grey

Ordering

EAN	5020963000645
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	36.87 lb 16.721 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	37 in 940 mm

Package Level 1 Height	17 in 432 mm
Package Level 1 Depth / Length	17 in 432 mm
Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Brand / Label	Adaptaflex
Color	Gray
Flexibility	High
Inside Diameter	11.8 mm
Material	Polyamide/Nylon 6
Nominal Size	16 mm
Number of Batteries	0
Outside Diameter	15.8 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Fine Pitch
Radius	35 mm
Special Functions	High Fatigue Life, Self Extinguishing, Halogen Free
UPC	786210258614

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PAFS16/GR/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PAFS16/GR/50M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

