

PRODUCT-DETAILS

PAFS16/LG/50M

STD WGT LT GRY NYL COND 50M



General Information

Extended Product Type	PAFS16/LG/50M
Product ID	7TCA296000R2190
EAN	5020963031076
Catalog Description	STD WGT LT GRY NYL COND 50M
Long Description	Standard Weight Conduit, Nominal Conduit Size 16mm, NW Conduit Size 13, Fine Conduit Pitch, Outside Diameter 15.8mm, Inside Diameter 11.8mm, Static Bend Radius 35mm, Reel Length 50 Meters, Polyamide (Nylon) 6, Light Grey

Ordering

EAN	5020963031076
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	4.19 lb 1.9 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Brand / Label	Adaptaflex
Color	Gray
Flexibility	High
Inside Diameter	11.8 mm
Material	Polyamide/Nylon 6
Nominal Size	16 mm
Number of Batteries	0
Outside Diameter	15.8 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Fine Pitch
Radius	35 mm
Special Functions	High Fatigue Life, Self Extinguishing, Halogen Free
UPC	786210268736

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PAFS16/LG/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PAFS16/LG/50M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

