

PRODUCT-DETAILS

S40/50M

STEEL CONDUIT 40MM 50M



Product image
not available

General Information

Extended Product Type	S40/50M
Product ID	7TCA296000R2525
EAN	5020963018121
Catalog Description	STEEL CONDUIT 40MM 50M
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 42.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 50 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963018121
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	41.28 lb 18.721 kg

Container Information

Package Level 1 Width	12 in 305 mm
Package Level 1 Height	16 in

	406 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 2 Units	1 piece
Package Level 2 Width	12.1 in 307 mm
Package Level 2 Height	16.1 in 409 mm
Package Level 2 Depth / Length	16.1 in 409 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	37.7 mm
Material	Galvanized Steel
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	42.5 mm
Product Name	FLEXIBLE METAL CONDUIT
Product Type	Low Fire Hazard Conduit
Radius	80 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210293882

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S40/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S40/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available