

PRODUCT-DETAILS

# S10/25M

## 25M X S10 CONDUIT



### General Information

Extended Product Type	S10/25M
Product ID	7TCA296010R0007
EAN	5020963003318
Catalog Description	25M X S10 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 10mm, Reel Length 25 Meters, Galvanised Steel General Purpose

### Ordering

EAN	5020963003318
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	5.51 lb 2.499 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Material	Galvanized Steel
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210239224

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S10/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S10/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

