

PRODUCT-DETAILS

S10/9/C

UNTHREADED FITTING FOR S10



General Information

Extended Product Type	S10/9/C
Product ID	7TCA296010R0010
EAN	5020963003363
Catalog Description	UNTHREADED FITTING FOR S10
Long Description	Nickel Plated Brass Smooth Entry Bushing, Nominal Conduit Size 10 Millimeters, Hole Size-9mm

Ordering

EAN	5020963003363
-----	---------------

Dimensions

Product Net Weight	.02 lb 9.07 g
--------------------	------------------

Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /
Length

1 in
25 mm

Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP40
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Smooth Entry Bushing
Size	9mm
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210251288

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S10/9/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S10/9/C

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

