

PRODUCT-DETAILS

# S12/25M

## 25M X S12 CONDUIT



### General Information

Extended Product Type	S12/25M
Product ID	7TCA296010R0022
EAN	5020963003387
Catalog Description	25M X S12 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 12mm, Outside Diameter 13.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters, Galvanised Steel General Purpose

### Ordering

EAN	5020963003387
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	33.02 lb 14.975 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

## Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	10.3 mm
Material	Galvanized Steel
Nominal Size	5/16 in
Number of Batteries	0
Outside Diameter	13.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	30 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210251325

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S12/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S12/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

