

PRODUCT-DETAILS

S12/50M

50M X S12 CONDUIT



General Information

| | |
|-----------------------|--|
| Extended Product Type | S12/50M |
| Product ID | 7TCA296010R0024 |
| EAN | 5020963003394 |
| Catalog Description | 50M X S12 CONDUIT |
| Long Description | Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 12mm, Outside Diameter 13.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 50 Meters, Galvanised Steel General Purpose |

Ordering

| | |
|-----|---------------|
| EAN | 5020963003394 |
|-----|---------------|

Dimensions

| | |
|----------------------------|--------------------|
| Product Net Depth / Length | 50 m |
| Product Net Weight | 12.79 lb 5.8 kg |

Container Information

| | |
|-----------------------|-----------------|
| Package Level 2 Units | 1 piece |
| Package Level 2 Width | 37 in 940 mm |

| | |
|--------------------------------|-----------------|
| Package Level 2 Height | 17 in 432 mm |
| Package Level 2 Depth / Length | 17 in 432 mm |

Additional Information

| | |
|---------------------|--|
| Application | Indoors / Outdoors - Light Industrial, Buildings |
| Brand / Label | Adaptaflex |
| Flexibility | Very High |
| Inside Diameter | 10.3 mm |
| Material | Galvanized Steel |
| Nominal Size | 5/16 in |
| Number of Batteries | 0 |
| Outside Diameter | 13.0 mm |
| Product Name | ADAPTAFLEX |
| Product Type | Low Fire Hazard Conduit |
| Radius | 30 mm |
| Special Functions | Very High UV Protection and Fatigue Life |
| UPC | 786210261133 |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | S12/50M |
| Declaration of Conformity - CE | 9AKK107492A9618 |
| Instructions and Manuals | S12/50M |

Classifications

| | |
|------------------------------------|-------------------------------------|
| ETIM 6 | EC001179 - Protective metallic hose |
| ETIM 7 | EC001179 - Protective metallic hose |
| UNSPSC | 39131706 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5535 >> Electrical conduit |

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

