

PRODUCT-DETAILS

S16/10M

10M X S16 CONDUIT



General Information

Extended Product Type	S16/10M
Product ID	7TCA296010R0032
EAN	5020963003455
Catalog Description	10M X S16 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 10 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963003455
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	4.01 lb 1.819 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	40 in 1016 mm

Package Level 2 Height	50 in 1270 mm
Package Level 2 Depth / Length	48 in 1219 mm
Package Level 3 Units	1 piece
Package Level 3 Width	40 in 1016 mm
Package Level 3 Height	50 in 1270 mm
Package Level 3 Depth / Length	48 in 1219 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	13.0 mm
Material	Galvanized Steel
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	16.0 mm
Product Name	FLEX STEEL CONDUIT
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210261393

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S16/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S16/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

