

PRODUCT-DETAILS

# S20/20/C

## UNTHREADED FITTING FOR S20



### General Information

Extended Product Type	S20/20/C
Product ID	7TCA296010R0062
EAN	5020963001239
Catalog Description	UNTHREADED FITTING FOR S20
Long Description	Nickel Plated Brass Smooth Entry Bushing, Nominal Conduit Size 20 Millimeters, Hole Size-20mm

### Ordering

EAN	5020963001239
-----	---------------

### Dimensions

Product Net Weight	.05 lb 22.676 g
--------------------	--------------------

### Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /  
Length

1 in  
25 mm

---

### Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP40
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Smooth Entry Bushing
Size	20mm
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210261515

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S20/20/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S20/20/C

---

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

