

PRODUCT-DETAILS

S25/10M

10M X S25 CONDUIT



General Information

Extended Product Type	S25/10M
Product ID	7TCA296010R0086
EAN	5020963001468
Catalog Description	10M X S25 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 10 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963001468
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	6.17 lb 2.798 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	21.4 mm
Material	Galvanized Steel
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	25.0 mm
Product Name	flex metal conduit
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210251462

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S25/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S25/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

