

PRODUCT-DETAILS

S25/25M

25M X S25 CONDUIT



General Information

Extended Product Type	S25/25M
Product ID	7TCA296010R0092
EAN	5020963000607
Catalog Description	25M X S25 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963000607
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	15.43 lb 6.998 kg

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	37 in 940 mm

Package Level 1 Height	17 in 432 mm
Package Level 1 Depth / Length	17 in 432 mm
Package Level 2 Units	10 piece
Package Level 2 Width	36 in 914 mm
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	21.4 mm
Material	Galvanized Steel
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	25.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210259451

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S25/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

