

PRODUCT-DETAILS

S25/50M-R

50M X S25 CONDUIT REELED



General Information

Extended Product Type	S25/50M-R
Product ID	7TCA296010R0095
EAN	5020963046711
Catalog Description	50M X S25 CONDUIT REELED
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 50 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963046711
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	31.48 lb 14.277 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	21.4 mm
Material	Galvanized Steel
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	25.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210261584

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S25/50M-R
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S25/50M-R

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

