

PRODUCT-DETAILS

S40/10M

10M X S40 CONDUIT



General Information

Extended Product Type	S40/10M
Product ID	7TCA296010R0136
EAN	5020963003622
Catalog Description	10M X S40 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 42.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 10 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963003622
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	16.51 lb 7.488 kg

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	420 in 10668 mm

Package Level 1 Height	415 in 10541 mm
Package Level 1 Depth / Length	415 in 10541 mm
Package Level 2 Units	15 piece
Package Level 2 Width	420 in 10668 mm
Package Level 2 Height	415 in 10541 mm
Package Level 2 Depth / Length	415 in 10541 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	37.7 mm
Material	Galvanized Steel
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	42.5 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	80 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210251554

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S40/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S40/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

