

PRODUCT-DETAILS

# S40/25M

## 25M X S40 CONDUIT



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | S40/25M  |
| Product ID            | 7TCA296010R0140  |
| EAN                   | 5020963003639  |
| Catalog Description   | 25M X S40 CONDUIT  |
| Long Description      | Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 42.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 25 Meters, Galvanised Steel General Purpose |

### Ordering

|     |               |
|-----|---------------|
| EAN | 5020963003639 |
|-----|---------------|

### Dimensions

|                            |                       |
|----------------------------|-----------------------|
| Product Net Depth / Length | 25 m                  |
| Product Net Weight         | 41.28 lb<br>18.721 kg |

### Container Information

|                       |                 |
|-----------------------|-----------------|
| Package Level 2 Units | 1 piece         |
| Package Level 2 Width | 37 in<br>940 mm |

|                                |                 |
|--------------------------------|-----------------|
| Package Level 2 Height         | 17 in<br>432 mm |
| Package Level 2 Depth / Length | 17 in<br>432 mm |

## Additional Information

|                     |  |
|---------------------|--|
| Application         | Indoors / Outdoors - Light Industrial, Buildings |
| Brand / Label       | Adaptaflex                                       |
| Flexibility         | Very High  |
| Inside Diameter     | 37.7 mm  |
| Material            | Galvanized Steel                                 |
| Nominal Size        | 1-1/4 in   |
| Number of Batteries | 0  |
| Outside Diameter    | 42.5 mm  |
| Product Name        | flexible metal conduit                           |
| Product Type        | Low Fire Hazard Conduit                          |
| Radius              | 80 mm  |
| Special Functions   | Very High UV Protection and Fatigue Life         |
| UPC                 | 786210251561                                     |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | S40/25M         |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| Instructions and Manuals          | S40/25M         |

## Classifications

|                                    |                                     |
|------------------------------------|-------------------------------------|
| ETIM 6                             | EC001179 - Protective metallic hose |
| ETIM 7                             | EC001179 - Protective metallic hose |
| UNSPSC                             | 39131706                            |
| WEEE Category                      | Product Not in WEEE Scope           |
| IDEA Granular Category Code (IGCC) | 5535 >> Electrical conduit          |

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

