

PRODUCT-DETAILS

S50/50M

50M S TYPE CONDUIT



Product image
not available

General Information

Extended Product Type	S50/50M
Product ID	7TCA296010R0159
EAN	5020963797637
Catalog Description	50M S TYPE CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 50mm, Outside Diameter 53.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 50 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963797637
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	53.96 lb 24.472 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	14 in 356 mm

Package Level 2 Height	14 in 356 mm
Package Level 2 Depth / Length	14 in 356 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	48.4 mm
Material	Galvanized Steel
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	53.0 mm
Product Name	FLEXIBLE METAL CONDUIT
Product Type	Low Fire Hazard Conduit
Radius	90 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210293752

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S50/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S50/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available