

PRODUCT-DETAILS

S50/51/C

UNTHREADED FITTING FOR S50



General Information

Extended Product Type	S50/51/C
Product ID	7TCA296010R0160
EAN	5020963003714
Catalog Description	UNTHREADED FITTING FOR S50
Long Description	Nickel Plated Brass Smooth Entry Bushing, Nominal Conduit Size 50 Millimeters, Hole Size-51mm

Ordering

EAN	5020963003714
-----	---------------

Dimensions

Product Net Weight	.43 lb 195.011 g
--------------------	---------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /
Length

1 in
25 mm

Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP40
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Smooth Entry Bushing
Size	51mm
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210251615

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S50/51/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S50/51/C

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

