

PRODUCT-DETAILS

S63/10M

10M X S63 CONDUIT



General Information

Extended Product Type	S63/10M
Product ID	7TCA296010R0169
EAN	5020963005275
Catalog Description	10M X S63 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 63mm, Outside Diameter 62.5mm, Inside Diameter 57.5mm, Static Bend Radius 115mm, Reel Length 10 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963005275
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	11.46 lb 5.197 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	57.5 mm
Material	Galvanized Steel
Nominal Size	2 in
Number of Batteries	0
Outside Diameter	62.5 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	115 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210251639

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S63/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S63/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

