

PRODUCT-DETAILS

# S75/10M

## 10M X S75 CONDUIT



### General Information

Extended Product Type	S75/10M
Product ID	7TCA296010R0187
EAN	5020963061196
Catalog Description	10M X S75 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 75mm, Outside Diameter 77.0mm, Inside Diameter 70.0mm, Static Bend Radius 150mm, Reel Length 10 Meters, Galvanised Steel General Purpose

### Ordering

EAN	5020963061196
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	33.62 lb 15.247 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	70.0 mm
Material	Galvanized Steel
Nominal Size	2-1/2 in
Number of Batteries	0
Outside Diameter	77.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	150 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210261720

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S75/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S75/10M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

