

PRODUCT-DETAILS

# STC10/25M

## STEEL T/COPPER BRD FLEX NC10 25M



### General Information

|                       |                                                                                                                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | STC10/25M                                                                                                                                                                                                                |
| Product ID            | 7TCA296010R0192                                                                                                                                                                                                          |
| EAN                   | 5020963047336                                                                                                                                                                                                            |
| Catalog Description   | STEEL T/COPPER BRD FLEX NC10 25M                                                                                                                                                                                         |
| Long Description      | Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 10mm, Outside Diameter 12.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 25 Meters, Galvanised Steel Core with Tinned Copper Overbraid |

### Ordering

|     |               |
|-----|---------------|
| EAN | 5020963047336 |
|-----|---------------|

### Dimensions

|                            |                     |
|----------------------------|---------------------|
| Product Net Depth / Length | 25 m                |
| Product Net Weight         | 5.51 lb<br>2.499 kg |

### Container Information

|                       |               |
|-----------------------|---------------|
| Package Level 2 Units | 1 piece       |
| Package Level 2 Width | 1 in<br>25 mm |

|                                |               |
|--------------------------------|---------------|
| Package Level 2 Height         | 1 in<br>25 mm |
| Package Level 2 Depth / Length | 1 in<br>25 mm |

### Additional Information

|                     |                                                    |
|---------------------|----------------------------------------------------|
| Application         | Galvanised Steel Core with Tinned Copper Overbraid |
| Brand / Label       | Adaptaflex                                         |
| Flexibility         | High                                               |
| Inside Diameter     | 6.8 mm                                             |
| Material            | Galvanized Steel Core with Tinned Copper Overbraid |
| Nominal Size        | 1/4 in<br>10 mm                                    |
| Number of Batteries | 0                                                  |
| Outside Diameter    | 12.0 mm                                            |
| Product Name        | flexible metal conduit                             |
| Product Type        | Low Fire Hazard Conduit                            |
| Radius              | 25 mm                                              |
| Special Functions   | Very High UV Protection                            |
| UPC                 | 786210249582                                       |

### Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | STC10/25M       |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| Instructions and Manuals          | STC10/25M       |

### Classifications

|                                    |                                     |
|------------------------------------|-------------------------------------|
| ETIM 6                             | EC001179 - Protective metallic hose |
| ETIM 7                             | EC001179 - Protective metallic hose |
| UNSPSC                             | 39131706                            |
| WEEE Category                      | Product Not in WEEE Scope           |
| IDEA Granular Category Code (IGCC) | 5535 >> Electrical conduit          |

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

