

PRODUCT-DETAILS

# SP10/BL/50M

## 50M X SP10/BLACK CONDUIT



### General Information

Extended Product Type	SP10/BL/50M
Product ID	7TCA296020R0029
EAN	5020963000980
Catalog Description	50M X SP10/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 10mm, Outside Diameter 10.0mm, Inside Diameter 6.8mm, Static Bend Radius 50mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

### Ordering

EAN	5020963000980
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	15.66 lb 7.102 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	40 in 1016 mm

Package Level 2 Height	50 in 1270 mm
Package Level 2 Depth / Length	48 in 1219 mm

## Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	6.8 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Outside Diameter	10.0 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	50 mm
UPC	786210259109

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP10/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP10/BL/50M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

