

PRODUCT-DETAILS

SP16/GR/50M

50M X SP16/GREY CONDUIT



General Information

Extended Product Type	SP16/GR/50M
Product ID	7TCA296020R0091
EAN	5020963052675
Catalog Description	50M X SP16/GREY CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 50 Meters, PVC Jacket with Galvanised Steel Core, Grey

Ordering

EAN	5020963052675
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	24.36 lb 11.048 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Gray
Flexibility	High
Inside Diameter	13.0 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	17.0 mm
Product Name	FLEX TUBING OF STEEL W/O FITTINGS
Product Type	High Flexibility Conduit
Radius	35 mm
UPC	786210295848

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP16/GR/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP16/GR/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

