

PRODUCT-DETAILS

# SP20/GR/25M

## 25M X SP20/GREY CONDUIT



### General Information

Extended Product Type	SP20/GR/25M
Product ID	7TCA296020R0147
EAN	5020963003080
Catalog Description	25M X SP20/GREY CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Grey

### Ordering

EAN	5020963003080
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	16.09 lb 7.297 kg

### Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	30 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Gray
Flexibility	High
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	45 mm
UPC	786210275567

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP20/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP20/GR/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

