

PRODUCT-DETAILS

SP20/OR/25M

25M X SP20/ORANGE CONDUIT



General Information

Extended Product Type	SP20/OR/25M
Product ID	7TCA296020R0161
EAN	5020963001284
Catalog Description	25M X SP20/ORANGE CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Orange

Ordering

EAN	5020963001284
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	16.31 lb 7.397 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	High
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	45 mm
UPC	786210259260

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP20/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP20/OR/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

