

1 in 25 mm

PRODUCT-DETAILS

Package Level 2 Height

## **SP25/075/M**NC25 SP25 M TYPE FITTING



General Information	
Extended Product Type	SP25/075/M
Product ID	7TCA296020R0174
EAN	5020963016905
Catalog Description	NC25 SP25 M TYPE FITTING
Long Description	Nickel Plated Brass Straight Fitting with Swivel External Thread, Nominal Conduit Size 25 Millimeters, 3/4 Inch NPT Thread
Ordoring	
Ordering	
EAN	5020963016905
Dimensions	
Product Net Weight	.24 lb 108.844 g
Container Information	
Package Level 2 Units	10 piece
Package Level 2 Width	1 in
	25 mm

Package Level 2 Depth / 1 in Length 25 mm

Additional Information		
Application	For Insertion into Threaded Entries or Knockout to Connect Conduit	
Brand / Label	Adaptaflex	
Cable Entry Position	3/4 Inch NPT Thread	
Color	Metallic	
Material	Brass	
Number of Batteries	0	
Product Name	ADAPTAFLEX	
Product Type	Conduit Fitting with NPT Threads	
Size	NC 25mm	
Surface Finishing	Nickel Plated	
UPC	786210275697	

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	SP25/075/M	
Declaration of Conformity - CE	9AKK107492A9618	
Instructions and Manuals	SP25/075/M	

Classifications		
ETIM 6	EC001180 - Screw connection for protective metallic hose	
ETIM 7	EC001180 - Screw connection for protective metallic hose	
UNSPSC	39121311	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings	

## **Categories**

 $Low\ Voltage\ Products\ \rightarrow\ Lost and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$ 

