

PRODUCT-DETAILS

# SP25/25/C

## UNTHREADED FITTING FOR SP25



### General Information

Extended Product Type	SP25/25/C
Product ID	7TCA296020R0176
EAN	5020963003158
Catalog Description	UNTHREADED FITTING FOR SP25
Long Description	Nickel Plated Brass Smooth Entry Bushing, Hole Size 1.00 Inch

### Ordering

EAN	5020963003158
-----	---------------

### Dimensions

Product Net Weight	.08 lb 36.281 g
--------------------	--------------------

### Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth /	1 in

Length	25 mm
--------	-------

### Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Smooth Entry Bushing
Size	3/4 Inch
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210249155

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP25/25/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP25/25/C

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

