

PRODUCT-DETAILS

SP25/BL/200M

200M X SP25/BLACK



General Information

Extended Product Type	SP25/BL/200M
Product ID	7TCA296020R0182
EAN	5020963024689
Catalog Description	200M X SP25/BLACK
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 200 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963024689
-----	---------------

Dimensions

Product Net Depth / Length	200 m
Product Net Weight	156.31 lb 70.889 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	55 mm
UPC	786210275635

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP25/BL/200M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP25/BL/200M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

