

PRODUCT-DETAILS

SP32/GR/100M

25M X SP32/GR COND



General Information

Extended Product Type	SP32/GR/100M
Product ID	7TCA296020R0240
EAN	5020963778070
Catalog Description	25M X SP32/GR COND
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 100 Meters, PVC Jacket with Galvanised Steel Core, Grey

Ordering

EAN	5020963778070
-----	---------------

Dimensions

Product Net Depth / Length	100 m
Product Net Weight	128.31 lb 58.19 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Gray
Flexibility	High
Inside Diameter	28.1 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1 in
Number of Batteries	0
Outside Diameter	34.0 mm
Product Name	metal flex conduit
Product Type	High Flexibility Conduit
Radius	60 mm
UPC	786210275727

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP32/GR/100M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP32/GR/100M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

