

PRODUCT-DETAILS

# SP40/OR/25M

## 25M X SP40/ORANGE CONDUIT



### General Information

Extended Product Type	SP40/OR/25M
Product ID	7TCA296020R0278
EAN	5020963007811
Catalog Description	25M X SP40/ORANGE CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 40mm, Outside Diameter 44.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Orange

### Ordering

EAN	5020963007811
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	52.36 lb 23.746 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	High
Inside Diameter	37.7 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	44.5 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	80 mm
UPC	786210259376

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP40/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP40/OR/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

