

PRODUCT-DETAILS

SP50/51/C

UNTHREADED FITTING FOR SP50



General Information

Extended Product Type	SP50/51/C
Product ID	7TCA296020R0286
EAN	5020963003264
Catalog Description	UNTHREADED FITTING FOR SP50
Long Description	Nickel Plated Brass Smooth Entry Bushing, Nominal Conduit Size 50 Millimeters, Hole Size 2.00 Inch

Ordering

EAN	5020963003264
-----	---------------

Dimensions

Product Net Weight	.36 lb 163.265 g
--------------------	---------------------

Container Information

Package Level 2 Units	2 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /
Length

1 in
25 mm

Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Smooth Entry Bushing
Size	1-1/2 Inch
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210249346

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP50/51/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP50/51/C

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

