

PRODUCT-DETAILS

SP50/BL/25M

25M X SP50/BLACK CONDUIT



General Information

Extended Product Type	SP50/BL/25M
Product ID	7TCA296020R0290
EAN	5020963000416
Catalog Description	25M X SP50/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 50mm, Outside Diameter 55.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963000416
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	63.71 lb 28.893 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	48.4 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	55.0 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	90 mm
UPC	786210249315

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP50/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP50/BL/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

