

PRODUCT-DETAILS

SP75/BL/25M

25M X SP75/BLACK CONDUIT



General Information

Extended Product Type	SP75/BL/25M
Product ID	7TCA296020R0337
EAN	5020963005527
Catalog Description	25M X SP75/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 75mm, Outside Diameter 79.0mm, Inside Diameter 70.0mm, Static Bend Radius 150mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963005527
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	101.19 lb 45.891 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	70.0 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	2-1/2 in
Number of Batteries	0
Outside Diameter	79.0 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	150 mm
UPC	786210275987

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP75/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP75/BL/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

