

PRODUCT-DETAILS

# SPHC75/10M

## HIGH/LOW TEMP. LQR CONDUIT10M



Product image  
not available

---

### General Information

Extended Product Type	SPHC75/10M
Product ID	7TCA296030R0036
EAN	5020963795343
Catalog Description	HIGH/LOW TEMP. LQR CONDUIT10M
Long Description	Liquid Tight Conduit for High/Low Temperatures, Nominal Conduit Size 75mm, Reel Length 10 Meters, Galvanised Steel Core, Black

---

### Ordering

EAN	5020963795343
-----	---------------

---

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	39.68 lb 17.995 kg

---

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Material	Galvanized Steel Core
Nominal Size	2-1/2 in NC75
Number of Batteries	0
Product Name	FLEX TUBING OF STEEL W/O FITTINGS
Product Type	High/Low Temperature Conduit
UPC	786210295169

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPHC75/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPHC75/10M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available