

PRODUCT-DETAILS

SPL10/50M

50M X SPL10/BLACK CONDUIT



General Information

Extended Product Type	SPL10/50M
Product ID	7TCA296030R0042
EAN	5020963001246
Catalog Description	50M X SPL10/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 10mm, Outside Diameter 11.8mm, Inside Diameter 7.0mm, Static Bend Radius 40mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963001246
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	17.86 lb 8.1 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	7.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/4 in NC10
Number of Batteries	0
Outside Diameter	11.8 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	40 mm
UPC	786210274867

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL10/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL10/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

