

PRODUCT-DETAILS

SPL10/E

SPL10/M/INSERT



General Information

Extended Product Type	SPL10/E
Product ID	7TCA296030R0043
EAN	5020963016943
Catalog Description	SPL10/M/INSERT
Long Description	Nickel Plated Brass Conduit Entry Gland, Nominal Conduit Size 10 Millimeters

Ordering

EAN	5020963016943
-----	---------------

Dimensions

Product Net Weight	.01 lb 4.535 g
--------------------	-------------------

Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth /	1 in

Length 25 mm

Additional Information

Application	Cable Protection at Conduit Entry / Exit Point
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	BASS FITTING FOR CONDUIT
Product Type	Conduit Terminator
Size	1/4 Inch
Special Functions	Very High UV Protection and High Degree of Mechanical Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -65 to +300 °C
UPC	786210258973

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL10/E
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL10/E

Classifications

ETIM 6	EC000814 - Threaded bush
ETIM 7	EC000814 - Threaded bush
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

