

PRODUCT-DETAILS

SPL16/100M

100M X SPL16/BLACK LQT CONDUIT



General Information

Extended Product Type	SPL16/100M
Product ID	7TCA296030R0075
EAN	5020963029004
Catalog Description	100M X SPL16/BLACK LQT CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 100 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963029004
-----	---------------

Dimensions

Product Net Depth / Length	100 m
Product Net Weight	67.68 lb 30.694 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	12.5 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	STEEL FLEX ELECT.CONDUIT PVC JACKET
Product Type	Oil Resistant Conduit
Radius	50 mm
UPC	786210239385

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL16/100M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL16/100M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

