

PRODUCT-DETAILS

# SPL16/50M

## 50M X SPL16/BLACK CONDUIT



### General Information

Extended Product Type	SPL16/50M
Product ID	7TCA296030R0080
EAN	5020963000782
Catalog Description	50M X SPL16/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

### Ordering

EAN	5020963000782
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	33.84 lb 15.347 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	12.5 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	flex metal conduit
Product Type	Oil Resistant Conduit
Radius	50 mm
UPC	786210246765

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL16/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL16/50M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

