

PRODUCT-DETAILS

SPL16/OR/25M

SPL16/ORANGE NC16 25M COILS



General Information

Extended Product Type	SPL16/OR/25M
Product ID	7TCA296030R0110
EAN	5020963008832
Catalog Description	SPL16/ORANGE NC16 25M COILS
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Orange

Ordering

EAN	5020963008832
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	16.92 lb 7.673 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	Medium
Inside Diameter	12.5 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	STEEL FLEX ELECT.CONDUIT PVC JACKET
Product Type	Oil Resistant Conduit
Radius	50 mm
UPC	786210239347

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL16/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL16/OR/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

