

PRODUCT-DETAILS

SPL20/100M

100M X SPL20



General Information

Extended Product Type	SPL20/100M
Product ID	7TCA296030R0136
EAN	5020963007453
Catalog Description	100M X SPL20
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 100 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963007453
-----	---------------

Dimensions

Product Net Depth / Length	100 m
Product Net Weight	87.75 lb 39.796 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	18 in 457 mm

Package Level 2 Height	30 in 762 mm
Package Level 2 Depth / Length	12 in 305 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	FLEXIBLE METAL CONDUIT CONNECTORS
Product Type	Oil Resistant Conduit
Radius	80 mm
UPC	786210239439

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL20/100M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL20/100M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

